

WONDERFIX

FLOOR, WALL TILE & STONE ADHESIVE

TILE ADHESIVE FOR **EASY** APPLICATION **LASTING** DURABILITY



Easy Application



Super Strength



Quick Setting



Ready to Use



Cost Effective



Non Toxic

A quick setting and high strength Tile Adhesive for wall & floor tiles, stones, granites & all kinds of claddings. Makes the application of the tiles etc simpler, faster and more reliable.



Pair it with Wonder Grout for the best finish. Available in 9 colours

Manufactured and Marketed by:
Golchha Paintoxide (P) Ltd.
C/4, Industrial Estate, Rourkela-769004 (Odisha)
9337400069, 8249469651
gp@golchhapigments.com
www.golchhapigments.com

Dealer:

DIRECTION OF USE



1 Clean the floor/wall surface to remove dust, oil & grease etc. properly so that there is no hindrance in adhesion.



5 Ensure that the tiles are fully supported by adhesive. Apply adhesive at back of tiles, if required to accommodate level.



2 Note that there must be a gap of 21 days from concrete casting or 5 days from cement plastering before tiling is done.



6 Tap the tiles gently with a wooden hammer after laying for proper fixing/leveling.




3 Mix WONDERFIX and clean water in the ratio of 5:1 by volume. Pour water in a container and add WONDERFIX slowly along with continuous stirring and mixing and prepare a consistent and thick mix.



7 Allow at least 24 hrs. time to gain proper bonding strength.



4 Apply the mix on the floor/wall surface in appropriate thickness using a trowel. 2mm bed thickness for wall and 3 mm for floor must be kept.



8 The bigger the size of tile, bigger is the notch of the trowel (from 1/4" to 1/2") and lesser is the coverage (4 to 8 sq.Mt.) Per 30 kg. Bag.



Other Quality Products from



GOLCHHA